



little dipper2 Static & drawDown Levels Specifications

Reel Assembly:	Small	Standard	Large
Height	19.5cm (7.7")	36cm (14.2")	50.5cm (20")
Depth	30.5cm (12")	21cm (8.3")	27.6cm (10.9")
Width	18.75cm (7.4")	29cm (11.4")	42cm (16.5")
Weight (Reel Assembly Only)	1.36kg. (2.9lb)	2.30kg (5.1lb)	4.56kg (10.05lbs)
Plate Size	26.67cm (10.5")	26.67cm (10.5")	30.5cm (12") 30.5cm (16")
Plate Material	Nylon	Nylon	Aluminum
Brake	Twist Lock		
Hanger	Included on frame leg	Included on frame leg	Included on frame leg
Tape Guide	No	Included on frame leg	No
Test Points	Separate (see instructions)	Use Conductive Material	On back of frame
Tape Lengths	15m, 50ft 22m, 75ft 30m, 100ft		
Tape:		Electronic Panel:	
Tape	High Tensile Steel	Operating Mode	Static & drawDown
Jacketing	Polyethylene	Power Source	9 Volt Alkaline
Conductors	7 strand (4 S/S & 3 copper)	Sensitivity Control	S/S & Aluminum
Markings	Metric or Engineering Scale - Under Jacketing	Audio/Visual Indication	Ultra Bright LED & 80dbi Buzzer
Width	.952cm (3/8")	Rating	IP65
Dog Bone Profile	Yes	Removable	YES
Break Strength	127kg (280lbs)	Maximum Temperature	80°C
Probe:		Included:	
Weight	106g (.233lbs)	Padded Carry Case	Included
Length	133.35mm (5.25")		
Diameter	16mm (.625")		
Removable	No	Warranty:	5 Year (Probe 1 Year)
Depth Rating	IP68		
Break Strain	68kg (150lbs)		
Wetted Material	S/S, Viton, Nylon, ABS & Teflon		